



SKF TMMP 6

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	120 mm
Alternative arm lengths	With accessory alternative arms: 220 mm or 370 mm or 470 mm
Claw height	15 mm
Claw length	19 mm
Total Arm length	221 mm
Claw width	8 mm
Spindle head, hexagon size	22
Total spindle length	362 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Pantograph mechanism for parallel opening of arms with selflocking function, heavy duty version. Alternative arm lengths available.
Number of arms	3
Pulling force (max)	60 kN
Spindle torque (max)	175 N·m
Spindle nose piece	Yes, ø20 mm
Цвет	Black
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Chemical blackened
Content	1x Puller TMMP 6; 1x Printed instructions for use

Логистика	
Масса нетто	4 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712