



SKF GEZ 208 ES-2RS

Radial spherical plain bearing, requiring maintenance, sealed, inch sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination and a double-lip contact seal on both sides. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Seal on both sides
Sealing type	Double-lip

Dimensions	
Bore diameter	63.5 mm
Outside diameter	100.013 mm
Width	55.55 mm
Width outer ring	47.625 mm
Angle of tilt	6 °
Raceway diameter inner ring	91.186 mm
Width annular lubrication groove at outer ring	9.1 mm
Width annular lubrication groove at inner ring	8 mm
Diameter lubrication hole (outer ring)	6.5 mm
Chamfer dimension bore	0.6 mm
Chamfer dimension outer ring	1 mm
Width, inner ring	55.55 mm
Width, outer ring	47.625 mm

Abutment dimensions	
Abutment diameter shaft	68.3 mm
Abutment diameter shaft	72.3 mm
Abutment diameter housing	87 mm
Abutment diameter housing	94.7 mm
Fillet radius shaft	0.6 mm
Fillet radius housing	1 mm

Calculation data	
Basic dynamic load rating	345 kN
Basic static load rating	1040 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	300 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	345 kN
Basic static load rating	1040 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN

Sealing	Seal on both sides
Sealing type	Double-lip
Relubrication feature	With

Logistics	
Product net weight	1.69 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings

