



SKF 3204 A-2ZTN9/MT33

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	20 mm
Outside diameter	47 mm
Width	20.6 mm
Recess diameter inner ring shoulder	27.7 mm
Recess diameter outer ring shoulder	40.9 mm
Chamfer dimension inner ring	1 mm
Distance pressure point(s)	28 mm
Contact angle	30 °

Abutment dimensions	
Abutment diameter shaft	25.6 mm
Abutment diameter shaft	27.5 mm
Abutment diameter housing	41.4 mm
Fillet radius	1 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	20.4 kN
Basic static load rating	12.9 kN
Fatigue load limit	0.55 kN
Reference speed	16000 r/min
Limiting speed	14000 r/min
Calculation factor	0.06
Limiting value	0.8
Calculation factor	0.63
Calculation factor	0.66
Calculation factor	0.78
Calculation factor	1.2

Performance	
Basic dynamic load rating	20.4 kN
Basic static load rating	12.9 kN
Reference speed	16000 r/min
Limiting speed	14000 r/min
SKF performance class	SKF Explorer

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel

Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.56 kg CO ₂ e

Logistics	
Product net weight	0.156 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings

