

SKF TMBS 50E

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Case dimensions (l x h x w)	295 x 190 x 50 mm
Total spindle length	138 mm
Свойства	
Покрытие	Black phosphated
Цвет	Black
Content	1 x separator set;1 x beam;1x mechanical spindle;2 x main rods;IFU QR code card;Case
Dismounting force generation	Spindle
Материал	Alloy engineering steels, hardened and tempered
Pulling force (max)	30 kN
Reach, using separator (max)	110 mm
Рекомендуемые применения	For dismounting of bearings, gears, pulleys and other industrial ring shaped components from shafts in industrial, construction and agricultural applications, where there is limited space behind the component and traditional jaw pullers won't fit.
Recommended storage temperature	Array °C
Relative humidity	max 75%
Separator height	16 mm
Shaft diameter range, using separator	7 to 50 mm
Special features	Provide the possibility to engage the inner ring of the bearing, thus making sure that no withdrawal force is transmitted through the rolling elements
Spindle head, hexagon size	19 mm
Spindle nose piece	no
Spindle torque (max)	70 N·m
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing type(s)	All
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for workpiece dismounting from a Housing	Нет
Workpiece outer diameter range, using separator	10 to 85 mm
Логистика	
Масса нетто	1.83 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712