



SKF W 607-2RS1

Stainless steel deep groove ball bearing with integral sealing

Stainless steel single row deep groove ball bearing with seals or shields on both sides, provide greater chemical and corrosion resistance. As with deep groove ball bearings generally, they are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

Technical specifications

Dimensions	
Bore diameter	7 mm
Outside diameter	19 mm
Width	6 mm
Recess diameter	9 mm
Recess diameter	16.5 mm
Chamfer dimension	0.3 mm

Abutment dimensions	
Diameter of shaft abutment	8.7 mm
Diameter of shaft abutment	8.9 mm
Diameter of housing abutment	17 mm
Radius of shaft or housing fillet	0.3 mm

Calculation data	
Basic dynamic load rating	1.53 kN
Basic static load rating	0.585 kN
Fatigue load limit	0.025 kN
Limiting speed	24000 r/min
Minimum load factor	0.03
Calculation factor	7.9

Performance	
Basic dynamic load rating	1.53 kN
Basic static load rating	0.585 kN
Limiting speed	24000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Stamped stainless steel
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Stainless steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.03 kg CO ₂ e

Logistics	
Product net weight	0.0072 kg
eClass code	23-05-08-01
UNSPSC code	31171504

SKF drawings