

# SKF 51320

## Single direction thrust ball bearing

Single direction thrust ball bearings can accommodate axial loads in one direction. They must not be subjected to any radial load. Their separable components facilitate mounting/dismounting and maintenance inspections. Many of the components are interchangeable. The shaft washers have a ground bore that enables an interference fit.



### Technical specifications

Dimensions	
Bore diameter	100 mm
Outside diameter	170 mm
Height	55 mm
Outside diameter shaft washer	170 mm
Inner diameter housing washer	103 mm
Chamfer dimension washer	1.5 mm

Abutment dimensions	
Abutment diameter shaft	142 mm
Abutment diameter housing	128 mm
Fillet radius	1.5 mm

Calculation data	
Basic dynamic load rating	225 kN
Basic static load rating	570 kN
Fatigue load limit	18.3 kN
Reference speed	1400 r/min
Limiting speed	1900 r/min
Minimum load factor	1.9

Performance	
Basic dynamic load rating	225 kN
Basic static load rating	570 kN
Reference speed	1400 r/min
Limiting speed	1900 r/min

Properties	
Axial load capability	Single-direction
Number of rows	1
Cage	Sheet metal
Housing washer type	Flat
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Indicative carbon footprint for new product	17.7 kg CO <sub>2</sub> e

Logistics	
Product net weight	4.92 kg
eClass code	23-05-10-01
UNSPSC code	31171507

**SKF drawings**

