

# SKF 51205

## Single direction thrust ball bearing

Single direction thrust ball bearings can accommodate axial loads in one direction. They must not be subjected to any radial load. Their separable components facilitate mounting/dismounting and maintenance inspections. Many of the components are interchangeable. The shaft washers have a ground bore that enables an interference fit.



### Technical specifications

Dimensions	
Bore diameter	25 mm
Outside diameter	47 mm
Height	15 mm
Outside diameter shaft washer	47 mm
Inner diameter housing washer	27 mm
Chamfer dimension washer	0.6 mm

Abutment dimensions	
Abutment diameter shaft	38 mm
Abutment diameter housing	34 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	26.5 kN
Basic static load rating	50 kN
Fatigue load limit	1.86 kN
Reference speed	5300 r/min
Limiting speed	7500 r/min
Minimum load factor	0.02

Performance	
Basic dynamic load rating	26.5 kN
Basic static load rating	50 kN
Reference speed	5300 r/min
Limiting speed	7500 r/min

Properties	
Axial load capability	Single-direction
Number of rows	1
Cage	Sheet metal
Housing washer type	Flat
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Indicative carbon footprint for new product	0.4 kg CO <sub>2</sub>

Logistics	
Product net weight	0.111 kg
eClass code	23-05-10-01
UNSPSC code	31171507

**SKF drawings**

