

SKF TMMP 10

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	207 mm
Alternative arm lengths	With accessory alternative arms: 350 mm or 460 mm or 710 mm
Claw height	20 mm
Claw length	26 mm
Total Arm length	335 mm
Claw width	10 mm
Spindle head, hexagon size	21
Total spindle length	516 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Pantograph mechanism for parallel opening of arms with selflocking function, heavy duty version. Alternative arm lengths available.
Number of arms	3
Pulling force (max)	100 kN
Spindle torque (max)	340 N·m
Spindle nose piece	Yes, ø24 mm
Цвет	Black
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Chemical blackened
Content	1x Puller TMMP 10; 1x Printed instructions for use

Логистика	
Масса нетто	8.5 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712