

## SKF 81105 TN

Single row cylindrical roller thrust bearing, single direction



Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

### Technical specifications

Dimensions	
Bore diameter	25 mm
Outside diameter	42 mm
Height	11 mm
Outside diameter shaft washer	42 mm
Bore diameter housing washer	26 mm
Height shaft washer	3 mm
Chamfer dimension housing washer	0.6 mm

Abutment dimensions	
Abutment diameter shaft	41 mm
Abutment diameter housing	26 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	25 kN
Basic static load rating	69.5 kN
Fatigue load limit	6.8 kN
Reference speed	3200 r/min
Limiting speed	6300 r/min
Minimum axial load factor	0.0004

Included products	
Roller and cage thrust assembly	K 81105 TN
Shaft washer	WS 81105
Housing washer	GS 81105

Performance	
Basic dynamic load rating	25 kN
Basic static load rating	69.5 kN
Reference speed	3200 r/min
Limiting speed	6300 r/min

Properties	
Bearing part	Complete bearing
Axial load capability	Single-direction
Number of rows	1
Cage	Non-metallic
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Indicative carbon footprint for new product	0.19 kg CO <sub>2</sub> e

Logistics	
Product net weight	0.052 kg
UNSPSC code	31171505

SKF drawings

