


SKF SY 40 TF



Pillow block ball bearing unit with extended inner ring and set screw locking, cast iron housing

Pillow (plummer) block ball bearing units consist of an insert bearing mounted in a cast iron housing that can be bolted to a support surface. This variant is suitable for applications with both constant and alternating directions of rotation. It has an inner ring extended on both sides and is locked onto the shaft by tightening a set screw on the inner ring, making it easy to mount.

Technical specifications

General	
Compliance with standard	ISO
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Optional end cover
Coating	Without
Dimensions	
Bore diameter	40 mm
Shoulder diameter of inner ring	51.8 mm
Base width	48 mm
Top width	30 mm
Standout of end cover	26 mm
Width of inner ring	49.2 mm
Distance from locking device side face to thread centre	8 mm
Height of spherical seat centre	49.2 mm
Foot height	19 mm
Overall height	99 mm
Distance between attachment bolts	135.5 mm
Maximum distance between attachment bolts	146 mm
Minimum distance between attachment bolts	125 mm
Overall length	175 mm
Diameter of attachment bolt hole	14 mm
Length of attachment bolt hole	24.5 mm
Distance from locking device side face to raceway centre	30.2 mm
Housing thread for the grease fitting	1/4-28 UNF
Axial position of the housing thread	3.5 mm
Angular position of the housing thread	45 °
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	161 mm
Axial offset of dowel pins	17 mm
Recommended diameter for dowel pins	4 mm
Attachment bolt diameter	12 mm
Shaft diameter	40 mm
Centre height (pillow block)	49.2 mm
Housing overall width	48 mm
Centre distance between bolt holes	135.5 mm
Bearing width, total	49.2 mm
Calculation data	
Basic dynamic load rating	30.7 kN
Basic static load rating	19 kN
Fatigue load limit	0.8 kN
Limiting speed	4800 r/min

Mounting information

Set screw	M8x1
Hexagonal key size for set screw	4 mm
Recommended tightening torque for set screw	6.5 N·m
Recommended diameter for attachment bolts, mm	12 mm
Recommended diameter for attachment bolts, inch	0.5 in

Performance

Basic dynamic load rating	30.7 kN
Basic static load rating	19 kN
Limiting speed	4800 r/min
Note	Limiting speed with shaft tolerance h6

Properties

Housing type	Pillow block, normal base
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics

Product net weight	1.84 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings

