



## SKF FYTWK 20 YTH

Oval flanged ball bearing unit with set screw locking and extended inner ring, co

These oval flanged ball bearing units are designed especially for the food and beverage industries. They are chemical resistant, lightweight and strong. The unit consists of an insert bearing, with an extended inner ring and set screw locking, and is suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a composite housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

### Technical specifications

General	
Compliance with standard	ISO with boundary dimension deviations
Purpose specific	For food and beverage applications
Material, housing	Composite for the SKF Food Line
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, multiple
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	20 mm
Outer diameter of inner ring	28.2 mm
Width of housing	29.5 mm
Flange width	15 mm
Width including end cover	26 mm
Width of inner ring	31 mm
Overall bearing width	31 mm
Distance from locking device side face to thread centre	4.5 mm
Top external diameter	59 mm
Overall height	112 mm
Centre distance between bolt holes	90 mm
Overall length	60.5 mm
Diameter of attachment bolt hole	12.3 mm
Distance from locking device side face to raceway centre	18.3 mm
Overall width	37.3 mm
Attachment bolt diameter	10 mm
Shaft diameter	20 mm
Housing overall width	29.5 mm
Bearing width, total	31 mm

Calculation data	
Basic dynamic load rating	10.8 kN
Basic static load rating	6.55 kN
Fatigue load limit	0.28 kN
Limiting speed	5000 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m
Recommended diameter for attachment bolts, mm	10 mm
Recommended diameter for attachment bolts, inch	0.375 in

Performance	
Basic dynamic load rating	10.8 kN
Basic static load rating	6.55 kN
Limiting speed	5000 r/min

Note	Limiting speed with shaft tolerance h6
------	--

<b>Properties</b>	
Housing type	Flanged
Flanged housing type	Oval
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Composite for the SKF Food Line
Material, bearing	Stainless steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, multiple
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	Without
Grease fitting	Without

<b>Logistics</b>	
Product net weight	0.244 kg

**SKF drawings**