

SKF HN 8-9

Hook spanner

The SKF Hook spanner, size 8 - 9, is designed for easy tightening and loosening of lock nuts. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. They fit on a variety of lock nuts with outer diameter(s) 58 - 65 mm. To be more specific for locknuts: KM 8, KM 9, KMK 8, KMK 9, KMFE 8, KMFE 9, KMT 8, N 08, N 09 and M38x1,5, M40x1,5, M42x1,5 (DIN 1804).

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _k)	7 mm
Nose height (N _h)	4 mm
Thickness (n)	7 mm
Length (L)	243 mm
Working length (l)	210 mm
Height (H)	46 mm

Properties	
Recommended applications	For applications that require tightening/loosening a wide variety of lock nuts on shafts, adapter sleeves, and withdrawal sleeves.
Series	Hook spanner, standard, HN
Type	Model B
Allows bearing mounting	Yes, angle method or with clearance reduction measurement
Size according DIN 1810	-
Fits on lock nuts inside SKF split pillow block housings (SNL)	No
Suitable SKF Locknut	KM 8, KM 9, KMFE 8, KMFE 9, KMFE 9 H, KMK 8, KMK 9, KMT 8, N 08
Material	Medium carbon steel, hardened and tempered
Material handle	Durable soft plastic
Coating	Black phosphated
Colour	Black, with red handle
Part of a kit	Yes, HN 4-16/SET

Logistics	
Product net weight	0.268 kg
eClass code	23-05-19-01
UNSPSC code	27111712