



## SKF NU 307 ECP/C3

Single row cylindrical roller bearing, NU design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

### Technical specifications

Dimensions	
Bore diameter	35 mm
Outside diameter	80 mm
Width	21 mm

  

Performance	
Basic dynamic load rating	75 kN
Basic static load rating	63 kN
Reference speed	9500 r/min
Limiting speed	11000 r/min
SKF performance class	SKF Explorer

  

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Non-metallic
Number of flanges, outer ring	2
Number of flanges, inner ring	0
Loose flange	None
Radial internal clearance	C3
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	1.7 kg CO <sub>2</sub>

  

Logistics	
Product net weight	0.473 kg
eClass code	23-05-09-01
UNSPSC code	31171505