


SKF FYTJ 506

Oval flanged housing for insert bearings, cast iron, JIS

These oval flanged housings for insert bearings are compliant with Japanese Industrial Standards (JIS). They are made of grey cast iron and can be bolted with two bolts to a machine wall or frame. They have been developed for bearing arrangements that must operate reliably in difficult environments.



Technical specifications

General	
Material	Cast iron

Dimensions	
Diameter of spherical seat	62 mm
Top external diameter	77 mm
Base external diameter	80 mm
Centering diameter	76.2 mm
Overall width	30.5 mm
Flange width	13.5 mm
Axial position of spherical seat (from support surface)	18 mm
Depth of centring recess	3.2 mm
Overall height	148 mm
Centre distance between bolt holes	117 mm
Overall length	80 mm
Diameter of attachment bolt hole	16 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	19 mm
Angular position of the housing thread	45 °
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of the grease fitting	1/4-28 SAE-LT
Distance of dowel pins	99 mm
Axial offset of dowel pins	12.5 mm
Recommended diameter for dowel pins	2 mm
Spherical seating diameter	62 mm
Housing overall width	30.5 mm

Mounting information	
Recommended diameter for attachment bolts, mm	14 mm
Recommended diameter for attachment bolts, inch	0.5625 in

Properties	
Housing type	Flanged
Flanged housing type	Oval
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Material, housing	Cast iron
Coating	Without
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	0.597 kg
eClass code	23-05-16-02
UNSPSC code	31171536

SKF drawings

