



SKF 58716

Radial shaft seal with double metal case, SKF Wave lip, for oil or grease

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. CRWH1 seals are designed with a double metal case, an SKF WAVE lip made of elastomer with a higher pumping rate to reduce heat generation, and a garter spring to optimize sealing against the shaft. Most of the seals feature the SKF Bore Tite coating on the outside diameter that helps fill small imperfections in the housing bore.

Technical specifications

| General | |
|--------------------------------------|--|
| Type of outside diameter | Metal-cased with sealant coating on the outside diameter |
| Lip material | Nitrile rubber (NBR) |
| Seal design | CRWH1 |
| Dimensions | |
| Shaft diameter | 149.23 mm |
| Housing bore diameter | 180.98 mm |
| Seal width | 12.7 mm |
| Application and operating conditions | |
| Operating temperature | -40 °C |
| Operating temperature | 100 °C |
| Circumferential speed | 12.3 m/s |
| Rotational speed | 1560 r/min |
| Pressure differential | 0.07 N/mm ² |
| Performance | |
| Limiting speed | 1560 r/min |
| Maximum operating temperature | 100 °C |
| Minimum operating temperature | -40 °C |
| Permissible circumferential speed | 12.3 m/s |
| Rotational speed | 1560 r/min |
| Properties | |
| Design | CRWH1 |
| Auxiliary lip | No |
| Sealing lip material | Nitrile rubber (NBR) |
| Type of outside diameter | Metal-cased with sealant coating on the outside diameter |
| Unit system | Inch |
| Logistics | |
| Product net weight | 0.221 kg |
| eClass code | 23-07-08-01 |
| UNSPSC code | 31181602 |

SKF drawings

