



## SKF 61801

### Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

## Technical specifications

Dimensions	
Bore diameter	12 mm
Deviation limits of mid-range bore diameter	-0.007..0 mm
Outside diameter	21 mm
Deviation limits of mid-range outside diameter	-0.008..0 mm
Width	5 mm
Deviation limits of ring width	-0.12..0 mm
Shoulder diameter	14.8 mm
Shoulder diameter	18.3 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	P6

Abutment dimensions	
Diameter of shaft abutment	14 mm
Diameter of housing abutment	19 mm
Radius of shaft or housing fillet	0.3 mm

Calculation data	
Basic dynamic load rating	1.74 kN
Basic static load rating	0.915 kN
Fatigue load limit	0.039 kN
Reference speed	70000 r/min
Limiting speed	43000 r/min
Minimum load factor	0.02
Calculation factor	13.4

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	7 µm
Range of section height at outer ring of assembled bearing	9 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	1.74 kN
Basic static load rating	0.915 kN
Reference speed	70000 r/min
Limiting speed	43000 r/min

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Without

Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.02 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.006 kg
eClass code	23-05-08-01
UNSPSC code	31171504

**SKF drawings**