

SKF TMMA 80

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	200 mm
Claw height	9.8 mm
Claw length	18 mm
Total Arm length	327 mm
Claw width	28 mm
Puller adaptor thread	UN 1.25 x 12 tpi
Spindle head, hexagon size	22
Puller or Adapter hexagon size	30 mm
Total spindle length	425 mm

Свойства	
Рекомендуемые применения	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Spring operated opening mechanism
Number of arms	3
Pulling force (max)	80 kN
Spindle torque (max)	175 N·m
Spindle nose piece	yes, ø26 mm
Цвет	Black, with red handle
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Black phosphated, red powdercoated
Content	1x Puller TMMA 80 with mechanical spindle; 1x Tube of spindle grease LGEV2/0.035; 1x Printed instructions for use

Логистика	
Масса нетто	5.68 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712