



## SKF 61902-2RS1

### Deep groove ball bearing with seals or shields

Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

## Technical specifications

Dimensions	
Bore diameter	15 mm
Deviation limits of mid-range bore diameter	-0.007..0 mm
Outside diameter	28 mm
Deviation limits of mid-range outside diameter	-0.008..0 mm
Width	7 mm
Deviation limits of ring width	-0.12..0 mm
Shoulder diameter	18.8 mm
Recess diameter	0 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	P6

  

Abutment dimensions	
Diameter of shaft abutment	17 mm
Diameter of shaft abutment	18.3 mm
Diameter of housing abutment	26 mm
Radius of shaft or housing fillet	0.3 mm

  

Calculation data	
Basic dynamic load rating	4.36 kN
Basic static load rating	2.24 kN
Fatigue load limit	0.095 kN
Limiting speed	16000 r/min
Minimum load factor	0.02
Calculation factor	14.3

  

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	7 µm
Range of section height at outer ring of assembled bearing	9 µm
ISO tolerance class for geometrical tolerances	P6

  

Performance	
Basic dynamic load rating	4.36 kN
Basic static load rating	2.24 kN
Limiting speed	16000 r/min

  

Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact

Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.06 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.0159 kg
eClass code	23-05-08-01
UNSPSC code	31171504

**SKF drawings**