



## SKF 25X52X7 HMSA10 V

Radial shaft seal with rubber outside diameter and single sealing lip, for oil or grease

Radial shaft seals are used between rotating and stationary machine components, or between components in relative motion. HMSA10 seals are designed with a rubber outside diameter. They have a conventional sealing lip made of elastomer. A garter spring in the seal and a non-contacting auxiliary lip optimize the sealing against the shaft also in polluted environment.

### Technical specifications

| General                  |                         |
|--------------------------|-------------------------|
| Type of outside diameter | Rubber metal reinforced |
| Lip material             | Fluoro rubber (FKM)     |
| Seal design              | HMSA10                  |
| Compliance with standard | ISO 6194; DIN 3760      |

| Dimensions            |       |
|-----------------------|-------|
| Shaft diameter        | 25 mm |
| Housing bore diameter | 52 mm |
| Seal width            | 7 mm  |

| Application and operating conditions |                        |
|--------------------------------------|------------------------|
| Operating temperature                | -25 °C                 |
| Operating temperature                | 200 °C                 |
| Operating temperature, short periods | 200 °C                 |
| Circumferential speed                | 17.4 m/s               |
| Rotational speed                     | 13320 r/min            |
| Pressure differential                | 0.05 N/mm <sup>2</sup> |

| Associated products |       |
|---------------------|-------|
| SKF Speedi-Sleeve   | 99098 |

| Performance                       |             |
|-----------------------------------|-------------|
| Limiting speed                    | 13320 r/min |
| Maximum operating temperature     | 200 °C      |
| Minimum operating temperature     | -25 °C      |
| Permissible circumferential speed | 17.4 m/s    |
| Rotational speed                  | 13320 r/min |

| Properties               |                         |
|--------------------------|-------------------------|
| Design                   | HMSA10                  |
| Auxiliary lip            | Yes                     |
| Sealing lip material     | Fluoro rubber (FKM)     |
| Type of outside diameter | Rubber metal reinforced |
| Unit system              | Metric                  |

| Logistics          |             |
|--------------------|-------------|
| Product net weight | 0.021 kg    |
| eClass code        | 23-07-08-01 |
| UNSPSC code        | 31181602    |

**SKF drawings**

