

SKF TKSA 11

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.



Характеристики

Свойства	
Alignment methods	3 position measurement 9 -12 -3
Рекомендуемые применения	Horizontal shafts
Live correction values	Only horizontal
Special features	Automatic .pdf reports
Sensors	2x Inductive proximity sensors with 3x reference bars
Communications	Bluetooth 4.0 LE
Measurement distance	0 to 185 mm between brackets
Measuring error (percent)	2 %
Материал	Measurement unit: PC/ABS plastic
Battery	Rechargeable 1900 mAh LiPo battery
Battery life	18 h
Температурный диапазон	Array °C
Display	None, Smartphone or tablet needed
Operating system	min. Android 9; min. Apple iOS 9
Software update	Via Apple AppStore and Google Play Store
Suitable operating devices	Android Tablet or Smartphone with min. Android 9; Apple iPad, iPhone with min. iOS 9
Laser type	Без
Mounting	2x V-brackets (width 15 mm) with chains
Shaft diameter	20 to 160 mm
Shaft diameter (with extension chains)	Up to 320 mm with optional extension chains (not included)
Maximum coupling height	55 mm
Power adapter	Charging via micro USB 2.0 port (5V); Micro USB to USB charging cable included; Compatible with standard 5V USB chargers (not included)
Degree of protection (IP)	IP 54
Certifications	Calibration certificate (2 years validity)
Part of a kit	no, but also available as TKSA 11/KIT380 or TKSA 11/KIT75
Case dimensions (l x h x w)	360 x 110 x 260 mm
Content	Measuring unit; 3 Reference bars; Set of 2 shaft brackets with chains 480 mm (18.9 in) and rods 80 mm (3.1 in); Micro USB to USB charging cable; Measuring tape; Certificate of calibration and conformance; Quick start guide; SKF carrying case

Логистика

Масса нетто	2.12 kg
Код eClass	23-05-19-01
Код UNSPSC	41112202