



SKF SI 10 E

Rod end, requires maintenance, female thread

These SKF rod ends contain a spherical plain bearing with a steel/steel sliding contact surface combination. The bearing requires maintenance and can only be relubricated from the side. The female thread is available with a left- (prefix SIL) or right-hand thread.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Without
Attachment feature, rod end shank	Right-hand female thread

Dimensions	
Bore diameter	10 mm
Diameter head	30 mm
Width inner ring	9 mm
Thread	M 10
Width head	7.5 mm
Height shank end face - centre rod end eye	43 mm
Angle of tilt	12 °
Raceway diameter inner ring	16 mm
Diameter shank	16 mm
Length thread	15 mm
Length (height) housing	60 mm
Length wrench flat	11 mm
Distance shank chamfer - centre rod end eye	14 mm
Size wrench	14 mm
Chamfer dimension bore	0.3 mm
Bore diameter, bearing inner ring	10 mm
Outside diameter, housing eye	30 mm
Width, bearing inner ring	9 mm
Thread designation	M 10
Width, housing eye	7.5 mm
Centre height, housing (from end of shank)	43 mm
Housing length, total	60 mm

Calculation data	
Basic dynamic load rating	8.15 kN
Basic static load rating	19 kN
Specific dynamic load factor	100 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	8.15 kN
Basic static load rating	19 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, housing	Steel
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required

Attachment feature, rod end shank	Right-hand female thread
Sealing	Without

Logistics	
Product net weight	0.068 kg
eClass code	23-05-01-05
UNSPSC code	31171508

SKF drawings

