



## SKF 6020

### Deep groove ball bearing

Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

## Technical specifications

<b>Dimensions</b>	
Bore diameter	100 mm
Deviation limits of mid-range bore diameter	-0.015..0 mm
Outside diameter	150 mm
Deviation limits of mid-range outside diameter	-0.015..0 mm
Width	24 mm
Deviation limits of ring width	-0.1..0 mm
Shoulder diameter	115.95 mm
Recess diameter	138.3 mm
Chamfer dimension	1.5 mm
ISO tolerance class for dimensions	P6 and tighter width tolerance

  

<b>Abutment dimensions</b>	
Diameter of shaft abutment	107 mm
Diameter of housing abutment	143 mm
Radius of shaft or housing fillet	1.5 mm

  

<b>Calculation data</b>	
SKF performance class	SKF Explorer
Basic dynamic load rating	63.7 kN
Basic static load rating	54 kN
Fatigue load limit	2.04 kN
Reference speed	9500 r/min
Limiting speed	5600 r/min
Minimum load factor	0.03
Calculation factor	15.9

  

<b>Tolerances of run-out</b>	
Range of section height at inner ring of assembled bearing	25 µm
Range of section height at outer ring of assembled bearing	40 µm
ISO tolerance class for geometrical tolerances	Normal

  

<b>Performance</b>	
Basic dynamic load rating	63.7 kN
Basic static load rating	54 kN
Reference speed	9500 r/min
Limiting speed	5600 r/min
SKF performance class	SKF Explorer

  

<b>Properties</b>	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel

Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	4.4 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	1.22 kg
eClass code	23-05-08-01
UNSPSC code	31171504

**SKF drawings**