



SKF YET 212

Insert bearing with an eccentric locking collar and narrow inner ring

Insert bearings are based on sealed deep groove ball bearings. This variant is intended for use in applications where the direction of rotation is constant. It has a narrow inner ring extended on one side, with an eccentric locking collar, enabling quick and easy mounting onto the shaft.

Technical specifications

Dimensions	
Bore diameter	60 mm
Outside diameter	110 mm
Overall bearing width	52.6 mm
Width of inner ring	36.7 mm
Width of outer ring	26 mm
Outside diameter of inner ring	75.64 mm
Outside diameter of locking collar	82 mm
Distance from side face to thread centre	7.95 mm
Chamfer dimension of inner ring	1.5 mm
Distance from locking device side face to raceway centre	39.6 mm
Shaft diameter	60 mm
Width, total	52.6 mm
Width, inner ring	36.7 mm
Width, outer ring	26 mm

Calculation data	
Basic dynamic load rating	52.7 kN
Basic static load rating	36 kN
Fatigue load limit	1.53 kN
Limiting speed	3400 r/min
	Limiting speed with shaft tolerance h6
Calculation factor	14

Mounting information	
Set screw	M10x1
Hexagonal key size for set screw	5 mm
Recommended tightening torque for set screw	16.5 N·m

Associated products	
Rubber seating ring	RIS 212 A

Performance	
Basic dynamic load rating	52.7 kN
Basic static load rating	36 kN
Limiting speed	3400 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Retaining feature, inner ring	Eccentric collar
Bore type	Cylindrical
Rolling elements	Balls
Outer ring type	Spherical
Inner ring extension	On one side
Cage	Non-metallic
Rubber seating ring	Without
Material, bearing	Bearing steel
Coating	Without

Sealing	Seal on both sides
Sealing type	Contact, standard
Lubricant	Grease
Relubrication feature	With

Logistics	
Product net weight	1.31 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings

