

SKF HN 24/SNL

Hook spanner for use inside split plummer (pillow) block housings

The unique protected design of this SKF Hook spanner, allows it to tighten and loosen lock nuts whilst these are inside SKF split plummer (pillow) block housings (SNL). Alternatively it can be used as regular hook spanner. They are used to secure and adjust bearings on tapered journals, adapter sleeves and withdrawal sleeves. The SKF hook spanner HN 24/SNL, is designed for nuts with an outer diameter of 155 mm. In particular for lock nuts of series KM 24, KMFE 24, KMT 24, N 026, AN 24 and M105x2, M110x2 (DIN 1804).

Technical specifications

Dimensions	
Locknut size	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _k)	12 mm
Nose height (N _h)	6 mm
Thickness (n)	12 mm
Length (L)	372 mm
Working length (l)	375 mm

Properties	
Recommended applications	Special designed tool for tightening/loosening lock nuts in split plummer (pillow) block housings, where space is the limiting factor. Alternative use is general bearing arrangements and of lock nuts on shafts, adapter sleeves, and withdrawal sleeves in a wide variety of applications.
Series	Hook spanner, for housings, HN SNL
Type	Model D
Allows bearing mounting	No
Fits on lock nuts inside SKF split pillow block housings (SNL)	Yes
Suitable SKF Locknut	KM 24, KMFE 24, KML 26, KMT 24, N 026, AN 24
Material	Medium carbon steel, hardened and tempered
Material handle	Steel
Coating	Black phosphated
Colour	Black metallic

Logistics	
Product net weight	1.35 kg
eClass code	23-05-19-01
UNSPSC code	27111712