



SKF NU 206 ECKP/C3

Single row cylindrical roller bearing, NU design, with tapered bore

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. The tapered bore enables the bearings to be mounted on a tapered shaft seat or on a cylindrical shaft seat using an adapter or withdrawal sleeve. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

Technical specifications

Dimensions	
Bore diameter	30 mm
Outside diameter	62 mm
Width	16 mm

Performance	
Basic dynamic load rating	44 kN
Basic static load rating	36.5 kN
Reference speed	13000 r/min
Limiting speed	14000 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Complete bearing
Axial displacement capability	In both directions
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Tapered 1:12
Cage	Non-metallic
Number of flanges, outer ring	2
Number of flanges, inner ring	0
Loose flange	None
Radial internal clearance	C3
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.72 kg CO ₂ e

Logistics	
Product net weight	0.2 kg
eClass code	23-05-09-01
UNSPSC code	31171505