



## SKF NUP 207 ECP

Single row cylindrical roller bearing, NUP design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and one integral flange and one loose flange ring on the inner ring, NUP design bearings can locate the shaft axially in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

### Technical specifications

| Dimensions                             |          |
|----------------------------------------|----------|
| Bore diameter                          | 35 mm    |
| Outside diameter                       | 72 mm    |
| Width                                  | 17 mm    |
| Shoulder diameter of inner ring        | 48.1 mm  |
| Shoulder diameter of outer ring        | 60.33 mm |
| Raceway diameter of inner ring         | 44 mm    |
| Chamfer dimension                      | 1.1 mm   |
| Chamfer dimension of loose flange ring | 0.6 mm   |

| Abutment dimensions          |         |
|------------------------------|---------|
| Diameter of spacer sleeve    | 41.8 mm |
| Diameter of shaft abutment   | 50 mm   |
| Diameter of housing abutment | 65.1 mm |
| Radius of fillet             | 1 mm    |

| Calculation data          |              |
|---------------------------|--------------|
| SKF performance class     | SKF Explorer |
| Basic dynamic load rating | 56 kN        |
| Basic static load rating  | 48 kN        |
| Fatigue load limit        | 6.1 kN       |
| Reference speed           | 11000 r/min  |
| Limiting speed            | 12000 r/min  |
| Minimum load factor       | 0.15         |
| Limiting value            | 0.2          |
| Calculation factor        | 0.6          |

| Performance               |              |
|---------------------------|--------------|
| Basic dynamic load rating | 56 kN        |
| Basic static load rating  | 48 kN        |
| Reference speed           | 11000 r/min  |
| Limiting speed            | 12000 r/min  |
| SKF performance class     | SKF Explorer |

| Properties                           |                         |
|--------------------------------------|-------------------------|
| Bearing part                         | Complete bearing        |
| Axial displacement capability        | None                    |
| Number of rows                       | 1                       |
| Locating feature, bearing outer ring | Without                 |
| Bore type                            | Cylindrical             |
| Cage                                 | Non-metallic            |
| Number of flanges, outer ring        | 2                       |
| Number of flanges, inner ring        | 1                       |
| Loose flange                         | Inner ring loose flange |
| Radial internal clearance            | CN                      |
| Tolerance class                      | Normal                  |
| Coating                              | Without                 |
| Sealing                              | Without                 |

|                                             |                          |
|---------------------------------------------|--------------------------|
| Lubricant                                   | None                     |
| Relubrication feature                       | Without                  |
| Indicative carbon footprint for new product | 1.1 kg CO <sub>2</sub> e |

| Logistics          |             |
|--------------------|-------------|
| Product net weight | 0.309 kg    |
| eClass code        | 23-05-09-01 |
| UNSPSC code        | 31171505    |

**SKF drawings**

