



## SKF 7201 BEGAP

### Single row angular contact ball bearing

These single row angular contact ball bearings can accommodate radial and axial loads acting simultaneously, where the axial load acts in one direction only. They can operate at high speeds and, depending on the variant, even very high speeds. They are more suitable than deep groove ball bearings for supporting large axial forces acting in one direction.

## Technical specifications

Dimensions	
Bore diameter	12 mm
Deviation limits of mid-range bore diameter	-0.007..0 mm
Outside diameter	32 mm
Deviation limits of mid-range outside diameter	-0.009..0 mm
Width	10 mm
Deviation limits of ring width	-0.12..0 mm
Shoulder diameter of inner ring (large side face)	20.2 mm
Shoulder diameter of inner ring (small side face)	16.57 mm
Shoulder diameter of outer ring (large side face)	25 mm
Distance side face to pressure point	14 mm
Chamfer dimension	0.6 mm
Chamfer dimension	0.3 mm
ISO tolerance class for dimensions	P6
Contact angle	40 °

Abutment dimensions	
Diameter of shaft abutment	16.2 mm
Abutment diameter housing	27.8 mm
Diameter of housing abutment	30 mm
Radius of fillet	0.6 mm
Radius of fillet	0.3 mm

Calculation data	
Basic dynamic load rating	7.61 kN
Basic static load rating	3.8 kN
Fatigue load limit	0.16 kN
Reference speed	28000 r/min
Limiting speed	26000 r/min
Minimum axial load factor	0.0003
Minimum radial load factor	0.1
Limiting value	1.1
Calculation factor (single, tandem)	0.35
Calculation factor (single, tandem)	0.26
Calculation factor (single, tandem)	0.57
Calculation factor (back-to-back, face-to-face)	0.57
Calculation factor (back-to-back, face-to-face)	0.52
Calculation factor (back-to-back, face-to-face)	0.55
Calculation factor (back-to-back, face-to-face)	0.93

Tolerances of run-out	
Range of section height at inner ring of assembled bearing	7 µm
Range of section height at outer ring of assembled bearing	10 µm
ISO tolerance class for geometrical tolerances	P6

Performance	
Basic dynamic load rating	7.61 kN
Basic static load rating	3.8 kN

Reference speed	28000 r/min
Limiting speed	26000 r/min

<b>Properties</b>	
Contact type	Normal contact (two-point contact)
Number of rows	1
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Matched arrangement	No
Universal matching bearing	Yes
Axial internal clearance	Not applicable
Matched condition (axial clearance/ preload)	Light preload
Tolerance class	Class 6 (P6)
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.13 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.0356 kg
eClass code	23-05-08-03
UNSPSC code	31171531

**SKF drawings**

