



SKF 3203 A-2RS1TN9

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	17 mm
Outside diameter	40 mm
Width	17.5 mm
Contact angle	30 °
Performance	
Basic dynamic load rating	14.3 kN
Basic static load rating	8.8 kN
Limiting speed	12000 r/min
Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without
Indicative carbon footprint for new product	0.35 kg CO ₂ e
Logistics	
Product net weight	0.096 kg
eClass code	23-05-08-03
UNSPSC code	31171531