

SKF TMMR 40F

Reversible jaw puller

The multi-purpose SKF Reversible Jaw Puller TMMR 40F is designed for internal and external pulling jobs of bearings and other components such as gears and pulleys. The two arms of the puller can be mounted with the claws facing inside or facing outside, making it a versatile and essential tool for mechanical workshops.

Technical specifications

Logistics	
Product net weight	0.33 kg
eClass code	23-05-19-01
UNSPSC code	27111712

Properties	
Recommended applications	For the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Yes
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Yes
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Yes
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	No
Suitable for workpiece dismounting from a Housing	Yes, with spindle support (not included)
Suitable for bearing type(s)	All
Dismounting force generation	Spindle
Special features	Reversible arms;Selflocking arms
Number of arms	2
Width of grip external	Array mm
Width of grip internal	Array mm
Effective arm length	67 mm
Total Arm length	103 mm
Claw height	4 mm
Claw length	6 mm
Claw width	13 mm
Spindle torque (max)	22 N·m
Spindle head, hexagon size	13
Puller or Adapter hexagon size	14 mm
Spindle nose piece	No
Material	Alloy engineering steels, hardened and tempered
Coating	Zinc coated
Content	1x Puller TMMR 40F;1x Tube of spindle grease LGV2/0.035;1x Printed instructions for use

Dimensions	
Total spindle length	133 mm