

SKF TMHP 15/260

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Width of grip external	Array mm
Effective arm length	264 mm
Alternative arm lengths	With accessory alternative arms: 344 or 439 or 689 mm
Claw height	30 mm
Claw length	37 mm
Total Arm length	449 mm
Claw width	12 mm
Spindle head, hexagon size	22 mm
Total spindle length	758 mm
Свойства	
Рекомендуемые применения	For the dismounting of larger bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Suitable for bearing type(s)	All
Dismounting force generation	A hydraulic pump is needed to advance the piston of the hydraulic cylinder in this puller, in which a mechanical spindle is fitted. The recommended pump TMJL to connect to the hydraulic cylinder, is included with this puller.
Special features	Pantograph mechanism for parallel opening of arms with selflocking, self centring function, heavy duty version; Spindle allows quick adjustment of the working length; Alternative arm lengths available.
Number of arms	3
Pulling force (max)	150 kN
Hydraulic Cylinder, piston stroke	100 mm
Hydraulic Cylinder, Maximum Operating Pressure	800 bar
Hydraulic Cylinder, Oil capacity	202 cm ³
Oil viscosity (maximum)	300 mm ² /s
Spindle nose piece	Yes, ø25 mm
Цвет	Black
Материал	Alloy engineering steels, hardened and tempered

Покрытие	Chemical blackened
Content	1x Puller TMHP 15/260;1x TMJL 100 Pump (complete in wooden carrying case);1x Printed instructions for use;1x Piston hold tool;1x Wooden storage crate

Логистика	
Масса нетто	57.4 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712