



SKF TKES 10A

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Свойства	
Температурный диапазон	Array °C
Рекомендуемые применения	inspection tool for internal inspection of machinery
Insertion Tube	Flexible tube with articulated tip
Adjustability	Fully flexible tube;300° tip articulation;330° rotatable neck
Light source	4x white LED with adjustable brightness
Tube length	1000 mm
Field of view	55 °
Depth of Field	Array mm
Special features	Comes with integrated magnets and tripod connection for handsfree use;TV out connection;Upto 2x digital zoom;USB out;Mirroring functions;Auto power-off; Sideview adapter included
Image resolution	320 x 240 pixels
Video resolution	320 x 240 pixels, 30 fps
Display	3.5" TFT LCD monitor with 320 x 240 pixels
Measurement method	CMOS
Memory	SD Card MB
Insertion tube and tip diameter	5.8 mm
Bending radius (min)	50 mm
Tripod connector	Yes, (1/4-20 UNC)
Battery	Rechargeable Li-Polymer Battery (3.7 V)
Battery life	4 h
Power adapter	Input: 100 - 240V 50/60 Hz EU/UK/US/AUS or via 5V USB 2.0 with cable included;Output: 5V DC 2A
Цвет	Blue,Black
Degree of protection (IP)	Tube: IP 67;Display device: IP 55
Case dimensions (l x h x w)	530 x 110 x 360 mm
Content	Display unit (TKES 10-DU);Articulated insertion tube 1m (TKES TA-1);SD memory card;Side view adapter 90° (TKES 1-M1);Video cable for s-video;Power adapter and charger with country plugs (TKES 10-CHARG);mini USB to USB cable;Cleaning accessories;Carrying case;Instructions for use;

Логистика	
Масса нетто	3.25 kg
Код eClass	23-05-19-01
Код UNSPSC	41112202