



SKF FY 45 WF

Square flanged ball bearing unit with eccentric locking, cast iron housing, ISO

These square flanged ball bearing units are compliant with ISO standards. They consist of an insert bearing, with an extended inner ring and eccentric locking, and are intended primarily for use in applications where the direction of rotation is constant. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	ISO
Purpose specific	For material handling applications; For air handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Optional end cover
Coating	Without

Dimensions	
Bore diameter	45 mm
Outer diameter of inner ring	56.8 mm
Outside diameter of locking ring	62 mm
Width of housing	39 mm
Flange width	14 mm
Depth of centring recess	3.2 mm
Standout of end cover	26.5 mm
Width of inner ring	42.8 mm
Overall bearing width	56.3 mm
Distance from locking device side face to thread centre	6.75 mm
Top external diameter	102 mm
Base external diameter	112 mm
Diameter of housing centering recess	119.1 mm
Centre distance between bolt holes	105 mm
Overall length	137 mm
Diameter of attachment bolt hole	16 mm
Distance from locking device side face to raceway centre	34.9 mm
Overall width	58.9 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	24.5 mm
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	123 mm
Axial offset of dowel pins	33.5 mm
Recommended diameter for dowel pins	4 mm
Attachment bolt diameter	14 mm
Shaft diameter	45 mm
Housing overall width	39 mm
Width, total	58.9 mm
Bearing width, total	56.3 mm

Calculation data	
Basic dynamic load rating	33.2 kN
Basic static load rating	21.6 kN
Fatigue load limit	0.915 kN
Limiting speed	4300 r/min

Mounting information

Set screw	M10x1
Hexagonal key size for set screw	5 mm
Recommended tightening torque for set screw	16.5 N·m
Recommended diameter for attachment bolts, mm	14 mm
Recommended diameter for attachment bolts, inch	0.5625 in

Performance

Basic dynamic load rating	33.2 kN
Basic static load rating	21.6 kN
Limiting speed	4300 r/min
Note	Limiting speed with shaft tolerance h6

Properties

Housing type	Flanged
Flanged housing type	Square
Number of bolt holes for fasteners	4
Fastening bolt hole type	Plain
Retaining feature, inner ring	Eccentric collar
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Optional end cover
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics

Product net weight	2.08 kg
eClass code	23-05-08-02
UNSPSC code	31171536

SKF drawings