



SKF 3205 A/C3

Double row angular contact ball bearing

Double row angular contact ball bearings correspond, in their design and operation, to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. They can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	25 mm
Outside diameter	52 mm
Width	20.6 mm
Contact angle	30 °

Performance	
Basic dynamic load rating	22 kN
Basic static load rating	15.3 kN
Reference speed	12000 r/min
Limiting speed	12000 r/min
SKF performance class	SKF Explorer

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	C3
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.62 kg CO ₂ e

Logistics	
Product net weight	0.172 kg
eClass code	23-05-08-03
UNSPSC code	31171531