



SKF 29317 E

Spherical roller thrust bearing with stamped steel cage

Spherical roller thrust bearings accommodate very heavy axial and considerable radial loads. They have the highest load rating of all thrust bearings, enabling compact, high power density bearing arrangements. By combining two or more spherical roller thrust bearings, it is possible to create a bearing arrangement that is either self-aligning, allowing misalignment of the shaft, or very stiff.

Technical specifications

Dimensions	
Bore diameter	85 mm
Outside diameter	150 mm
Height	39 mm
Outside diameter of shaft washer end side face	134 mm
Shoulder diameter outer ring	110 mm
Width shaft washer or length of shaft washer bore diameter that fits on shaft (bearings with a stamped steel cage)	24.5 mm
Height shaft washer + cage	33.8 mm
Height housing washer	20 mm
Distance from shaft washer end side face to pressure point	50 mm
Chamfer dimension shaft washer	1.5 mm

Abutment dimensions	
Diameter of shaft abutment	115 mm
Abutment diameter of spacer ring	90 mm
Outside diameter of spacer ring	90 mm
Diameter of housing abutment	129 mm
Fillet radius	1.5 mm

Calculation data	
Basic dynamic load rating	380 kN
Basic static load rating	1060 kN
Fatigue load limit	129 kN
Reference speed	2400 r/min
Limiting speed	4000 r/min
Minimum axial load factor	0.11

Performance	
Basic dynamic load rating	380 kN
Basic static load rating	1060 kN
Reference speed	2400 r/min
Limiting speed	4000 r/min
SKF performance class	SKF Explorer

Properties	
Locating feature, housing washer	None
Bore type	Cylindrical
Cage	Sheet metal
Tolerance class	Normal
Indicative carbon footprint for new product	9.9 kg CO ₂

Logistics	
Product net weight	2.76 kg
eClass code	23-05-11-03
UNSPSC code	31171507

SKF drawings

