



SKF 3200 A-2RS1TN9/MT33

Double row angular contact ball bearing with seals or shields

Double row angular contact ball bearings, with seals or shields, correspond to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. Depending on the sealing execution, they can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.

Technical specifications

Dimensions	
Bore diameter	10 mm
Outside diameter	30 mm
Width	14 mm
Recess diameter inner ring shoulder	15.8 mm
Recess diameter outer ring shoulder	24.95 mm
Chamfer dimension inner ring	0.6 mm
Distance pressure point(s)	16 mm
Contact angle	30 °

Abutment dimensions	
Abutment diameter shaft	14.4 mm
Abutment diameter shaft	15.5 mm
Abutment diameter housing	25.6 mm
Fillet radius	0.6 mm

Calculation data	
Basic dynamic load rating	7.61 kN
Basic static load rating	4.3 kN
Fatigue load limit	0.183 kN
Limiting speed	17000 r/min
Calculation factor	0.06
Limiting value	0.8
Calculation factor	0.63
Calculation factor	0.66
Calculation factor	0.78
Calculation factor	1.2

Performance	
Basic dynamic load rating	7.61 kN
Basic static load rating	4.3 kN
Limiting speed	17000 r/min

Properties	
Contact type	Normal contact (two-point contact)
Number of rows	2
Locating feature, bearing outer ring	Without
Ring type	One-piece inner and outer rings
Cage	Non-metallic
Arrangement of contact angle (double-row bearing)	Back-to-back (O)
Matched arrangement	No
Universal matching bearing	No
Axial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease

Relubrication feature	Without
Indicative carbon footprint for new product	0.18 kg CO ₂ e

Logistics	
Product net weight	0.0505 kg
eClass code	23-05-08-03
UNSPSC code	31171531

SKF drawings