


## SKF KRV 40 PP



Cam follower (stud-type track roller) with integral sealing and relubrication feature

Cam followers (stud-type track rollers) are designed to run on all types of tracks and to be used in cam drives, conveyor systems, etc. They are based on a needle roller bearing with a threaded solid stud instead of an inner ring. They have a thick-walled outer ring with a crowned running surface and are supplied sealed and ready-to-mount. The bearings can be relubricated via the stud.

### Technical specifications

Dimensions	
Outside diameter	40 mm
Attachment diameter	18 mm
Total length	58.1 mm
Width outer ring	20 mm
Length shank on stud	36.5 mm
Distance lubrication hole to flange ring	8 mm
Distance face outer ring to face side washer	0.8 mm
Outside diameter flange ring	30.7 mm
Thread stud	M18x1.5
Length thread	19 mm
Seat diameter for lubrication accessories	6 mm
Diameter of lubrication hole (shank)	3 mm
Width across flats	8 mm
Functional outside diameter	40 mm
Stud diameter	18 mm
Length	58.1 mm
Width, outer ring	20 mm

Calculation data	
Basic dynamic load rating	14 kN
Basic static load rating	31 kN
Fatigue load limit	3.65 kN
Maximum dynamic radial loads	19 kN
Maximum static radial loads	27 kN
Limiting speed	2000 r/min

Mounting information	
Recommended tightening torque	87 N·m

Included products	
Grease fitting	NIP B2x8
Hexagonal nut	M 18x1.5

Performance	
Basic dynamic load rating	14 kN
Basic static load rating	31 kN
Limiting speed	2000 r/min

Properties	
Rolling elements	Needle rollers
Number of rows	1
Outer ring profile	Crowned
Stud alignment	Centric
Number of flanges, outer ring	2
Feature for tightening	Hexagonal recess
Cage	Without
Radial internal clearance	Between C2 and CN

Tolerance class	Other
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Centre of each stud end and radial hole in stud shank

<b>Logistics</b>	
Product net weight	0.298 kg
eClass code	23-05-09-03
UNSPSC code	31171512

**SKF drawings**

