



SKF GEH 40 ES-2LS

Radial spherical plain bearing, requiring maintenance, sealed, metric sizes

These radial spherical plain bearings have a steel/steel sliding contact surface combination and a triple-lip, heavy-duty contact seal on both sides. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings. Compared to the GE series, they have a wider inner ring and a larger outside diameter, which enable higher load ratings and larger tilt angles.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Seal on both sides
Sealing type	Triple-lip

Dimensions	
Bore diameter	40 mm
Outside diameter	68 mm
Width	40 mm
Width outer ring	25 mm
Angle of tilt	17 °
Raceway diameter inner ring	60 mm
Width annular lubrication groove at outer ring	4.6 mm
Width annular lubrication groove at inner ring	4.8 mm
Diameter lubrication hole (outer ring)	3 mm
Chamfer dimension bore	0.6 mm
Chamfer dimension outer ring	1 mm
Width, inner ring	40 mm
Width, outer ring	25 mm

Abutment dimensions	
Abutment diameter shaft	44.1 mm
Abutment diameter shaft	44.7 mm
Abutment diameter housing	61 mm
Abutment diameter housing	63.6 mm
Fillet radius shaft	0.6 mm
Fillet radius housing	1 mm

Calculation data	
Basic dynamic load rating	127 kN
Basic static load rating	640 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	500 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	127 kN
Basic static load rating	640 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN

Sealing	Seal on both sides
Sealing type	Triple-lip
Relubrication feature	With

Logistics	
Product net weight	0.516 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings

