



SKF NA 4903.2RS

Single row needle roller bearing with machined rings, with flanges and integral seals

Single row needle roller bearings incorporate cylindrical rollers that are small in diameter relative to their length. Owing to their large number of rollers, the bearings have a high load carrying capacity. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication. The inner ring contains an additional lubrication hole.

Technical specifications

Dimensions	
Bore diameter	17 mm
Outside diameter	30 mm
Width	14 mm
Width outer ring	13 mm
Raceway diameter inner ring	22 mm
Chamfer dimension outer ring	0.3 mm
Permissible axial displacement from the normal position of one bearing ring relative to the other	0.5 mm

Abutment dimensions	
Smallest permissible abutment diameter shaft, bearings with flanges	19 mm
Diameter of housing abutment	28 mm
Fillet radius	0.3 mm

Calculation data	
Basic dynamic load rating	9.52 kN
Basic static load rating	12.9 kN
Fatigue load limit	1.53 kN
Limiting speed	9000 r/min

Performance	
Basic dynamic load rating	9.52 kN
Basic static load rating	12.9 kN
Limiting speed	9000 r/min

Properties	
Bearing part	Complete bearing
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet metal
Number of flanges, outer ring	2
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	With
Indicative carbon footprint for new product	0.15 kg CO ₂ e

Logistics	
Product net weight	0.0403 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings

