

SKF HNA 14-24

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.



Характеристики

Размеры	
Размер гайки	Array
Outer diameter lock nut (range) (d ₃)	Array mm
Nose width (N _к)	12 mm
Nose height (N _н)	5.5 mm
Thickness (n)	12 mm
Длина (L)	332 mm
Working length (l)	275 mm
Высота (H)	83 mm

Свойства	
Рекомендуемые применения	A versatile tool, covering multiple lock nut sizes, when working with of lock nuts on shafts, adapter sleeves, and withdrawal sleeves in various applications.
Серия	Hook spanner, adjustable, HN A
Тип	Model C
Allows bearing mounting	Нет
Fits on lock nuts inside SKF split pillow block housings (SNL)	Нет
Подходящие гайки SKF	KM 14, KM 15, KM 16, KM 17, KM 18, KM 19, KM 20, KM 22, KM 24, KMF 14, KMF 15, KMF 16, KMF 17, KMF 18, KMF 19, KMF 19, KMF 20, KMFE 14, KMFE 15, KMFE 15 H, KMFE 16, KMFE 17, KMFE 18, KMFE 19, KMFE 20, KMFE 21, KMFE 22, KMFE 24, KMK 13, KMK 15, KMK 16, KMK 17, KMK 18, KMK 19, KMK 20, KML 24, KML 26, KMT 13, KMT 14, KMT 15, KMT 16, KMT 17, KMT 18, KMT 19, KMT 20, KMT 20, KMT 22, KMT 24, KMT 24, N 14, N 15, N 16, N 17, N 18, N 19, N 20, N 21, N 22, N 24, N 022, N 024, AN 15, AN 16, AN 17, AN 18, AN 19, AN 20, AN 21, AN 22, AN 24
Материал	Medium carbon steel, hardened and tempered
Material handle	Durable soft plastic
Покрытие	Black oxide
Цвет	Black, with blue handle

Логистика	
Масса нетто	0.6 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712