



SKF GE 260 ES-2RS

Radial spherical plain bearing, requiring maintenance, sealed, metric sizes

Radial spherical plain bearings are designed to accommodate radial and combined radial and axial loads, and also misalignment. This specific design includes a steel/steel sliding contact surface combination and a double-lip contact seal on both sides. The bearings require maintenance and can be relubricated via lubrication holes and an annular groove in both rings.

Technical specifications

General	
Maintenance	Relubrication required
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Sealing	Seal on both sides
Sealing type	Double-lip

Dimensions	
Bore diameter	260 mm
Outside diameter	370 mm
Width	150 mm
Width outer ring	110 mm
Angle of tilt	7 °
Raceway diameter inner ring	325 mm
Width annular lubrication groove at outer ring	16 mm
Width annular lubrication groove at inner ring	16 mm
Diameter lubrication hole (outer ring)	7 mm
Chamfer dimension bore	1.1 mm
Chamfer dimension outer ring	1.1 mm
Width, inner ring	150 mm
Width, outer ring	110 mm

Abutment dimensions	
Abutment diameter shaft	273 mm
Abutment diameter shaft	288 mm
Abutment diameter housing	321.5 mm
Abutment diameter housing	359 mm
Fillet radius shaft	1 mm
Fillet radius housing	1 mm

Calculation data	
Basic dynamic load rating	3050 kN
Basic static load rating	15300 kN
Specific dynamic load factor	100 N/mm ²
Specific static load factor	500 N/mm ²
Material constant	330

Performance	
Basic dynamic load rating	3050 kN
Basic static load rating	15300 kN

Properties	
Sliding contact surface combination	Steel/steel, standard
Material, inner ring	Bearing steel
Material, outer ring	Bearing steel
Maintenance	Relubrication required
Radial internal clearance	CN

Sealing	Seal on both sides
Sealing type	Double-lip
Relubrication feature	With

Logistics	
Product net weight	51.5 kg
eClass code	23-05-01-06
UNSPSC code	31171515

SKF drawings