



SKF 32226

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	4FD
Dimensions	
Bore diameter	130 mm
Outside diameter	230 mm
Bearing width, total	67.75 mm
Shoulder diameter of inner ring	176 mm
Width of inner ring	64 mm
Width of outer ring	54 mm
Chamfer dimension of inner ring	4 mm
Chamfer dimension of outer ring	3 mm
Distance side face to pressure point	55.55 mm
Width, total	67.75 mm
Width, inner ring	64 mm
Width, outer ring	54 mm
Contact angle	16.2 °
Abutment dimensions	
Diameter of shaft abutment	146 mm
Diameter of shaft abutment	146.5 mm
Diameter of housing abutment	193 mm
Diameter of housing abutment	216.5 mm
Diameter of housing abutment	219 mm
Minimum width of space required in housing on large side face	7 mm
Minimum width of space required in housing on small side face	13.5 mm
Radius of shaft fillet	4 mm
Radius of housing fillet	3 mm
Calculation data	
Basic dynamic load rating	590 kN
Basic static load rating	830 kN
Fatigue load limit	85 kN
Reference speed	2000 r/min
Limiting speed	2800 r/min
Limiting value	0.43
Calculation factor	1.4
Calculation factor	0.8
Performance	
Basic dynamic load rating	590 kN
Basic static load rating	830 kN
Reference speed	2000 r/min
Limiting speed	2800 r/min
Properties	
Bearing part	Complete bearing
Number of rows	1

Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	40.7 kg CO ₂ e

Logistics	
Product net weight	11.3 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings