



SKF RNA 4910.2RS

Single row needle roller bearing with machined rings, with flanges and integral seals

Single row needle roller bearings without an inner ring consist of an outer ring with a needle roller and cage assembly. They are an excellent choice for compact bearing arrangements in applications where hardened and ground raceways can be provided on the shaft. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.

Technical specifications

Dimensions	
Diameter under rollers	58 mm
Outside diameter	72 mm
Width	22 mm
Chamfer dimension outer ring	0.6 mm
Bore diameter of needle roller complement	58 mm

Abutment dimensions	
Diameter of housing abutment	68 mm
Fillet radius	0.6 mm

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	46.5 kN
Basic static load rating	69.5 kN
Fatigue load limit	8.8 kN
Reference speed	7000 r/min
Limiting speed	3400 r/min

Performance	
Basic dynamic load rating	46.5 kN
Basic static load rating	69.5 kN
Reference speed	7000 r/min
Limiting speed	3400 r/min
SKF performance class	SKF Explorer

Properties	
Bearing part	Bearing without inner ring
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet steel
Number of flanges, outer ring	2
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	With
Indicative carbon footprint for new product	0.6 kg CO ₂ e

Logistics	
Product net weight	0.166 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings