



SKF 32228

Single row tapered roller bearing

Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

Technical specifications

General	
Dimension series	4FD
Dimensions	
Bore diameter	140 mm
Outside diameter	250 mm
Bearing width, total	71.75 mm
Shoulder diameter of inner ring	191.4 mm
Width of inner ring	68 mm
Width of outer ring	58 mm
Chamfer dimension of inner ring	4 mm
Chamfer dimension of outer ring	3 mm
Distance side face to pressure point	59.55 mm
Width, total	71.75 mm
Width, inner ring	68 mm
Width, outer ring	58 mm
Contact angle	16.2 °
Abutment dimensions	
Diameter of shaft abutment	159 mm
Diameter of shaft abutment	156.5 mm
Diameter of housing abutment	210 mm
Diameter of housing abutment	236.5 mm
Diameter of housing abutment	238 mm
Minimum width of space required in housing on large side face	8 mm
Minimum width of space required in housing on small side face	13.5 mm
Radius of shaft fillet	4 mm
Radius of housing fillet	3 mm
Calculation data	
Basic dynamic load rating	691 kN
Basic static load rating	1000 kN
Fatigue load limit	100 kN
Reference speed	1900 r/min
Limiting speed	2600 r/min
Limiting value	0.43
Calculation factor	1.4
Calculation factor	0.8
Performance	
Basic dynamic load rating	691 kN
Basic static load rating	1000 kN
Reference speed	1900 r/min
Limiting speed	2600 r/min
Properties	
Bearing part	Complete bearing
Number of rows	1

Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Sheet metal
Arrangement of contact angle (double-row bearing)	Not applicable
Matched arrangement	No
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Unit system	Metric
Indicative carbon footprint for new product	51.2 kg CO ₂ e

Logistics	
Product net weight	14.2 kg
eClass code	23-05-09-10
UNSPSC code	31171516

SKF drawings