

SKF TMMS 50

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Логистика	
Масса нетто	0.514 kg
Код eClass	23-05-19-01
Код UNSPSC	27111712

Свойства	
Рекомендуемые применения	For use with a puller in the dismounting of bearings, gears, pulleys and other industrial ring shaped components in industrial, construction and agricultural applications with an interference fit on the shaft. To assist a three armed puller where the claws of the puller can't grip the component properly.
Suitable for workpiece dismounting from a Cylindrical seating (straight shaft)	Да
Pulling force (max)	80 kN
Suitable for bearing dismounting from a Tapered seating (conical shaft)	Да
Suitable for bearing dismounting from a Sleeve (adapter or withdrawal sleeve)	Да
Suitable for workpiece dismounting from a Blind arrangement (housing with shaft)	Нет
Suitable for workpiece dismounting from a Housing	Нет
Dismounting force generation	by pullerarms
Section plates provided with threaded pullinghole	Нет
Материал	Alloy engineering steels, hardened and tempered
Покрытие	Rods: black phosphated; Plates and nuts, Zinc coated
Цвет	Metallic and black

Размеры	
Width of grip external	Array mm
Pulling rod distance	Array mm
Plate width	32 mm
Plate height	15 mm
Plate tip width	4 mm
Plate tip height	2 mm