



SKF 23134 CCK/C4W33

Spherical roller bearing with tapered bore and relubrication features

Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

Technical specifications

Dimensions	
Bore diameter	170 mm
Outside diameter	280 mm
Width	88 mm

Performance	
Basic dynamic load rating	1086 kN
Basic static load rating	1500 kN
Reference speed	1800 r/min
Limiting speed	2400 r/min
SKF performance class	SKF Explorer

Properties	
Number of rows	2
Locating feature, bearing outer ring	Without
Bore type	Tapered 1:12
Cage	Sheet metal
Radial internal clearance	C4
Tolerance class for dimensions	Normal
Tolerance class for run-out	P5
Sealing	Without
Lubricant	None
Relubrication feature	With
Candidate for remanufacturing	Yes
Indicative carbon footprint for new product	73.8 kg CO ₂ e
Indicative carbon footprint for remanufactured product	25.8 kg CO ₂ e

Logistics	
Product net weight	20.5 kg
eClass code	23-05-09-11
UNSPSC code	31171510