



SKF NKI 10/16

Single row needle roller bearing with machined rings, with flanges

Single row needle roller bearings incorporate cylindrical rollers that are small in diameter relative to their length. Owing to their large number of rollers, the bearings have a high load carrying capacity. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.

Technical specifications

Dimensions	
Bore diameter	10 mm
Outside diameter	22 mm
Width	16 mm
Raceway diameter inner ring	14 mm
Chamfer dimension outer ring	0.3 mm
Permissible axial displacement from the normal position of one bearing ring relative to the other	0.5 mm

Abutment dimensions	
Smallest permissible abutment diameter shaft, bearings with flanges	12 mm
Diameter of housing abutment	20 mm
Fillet radius	0.3 mm

Calculation data	
Basic dynamic load rating	10.2 kN
Basic static load rating	12.5 kN
Fatigue load limit	1.5 kN
Reference speed	24000 r/min
Limiting speed	28000 r/min

Performance	
Basic dynamic load rating	10.2 kN
Basic static load rating	12.5 kN
Reference speed	24000 r/min
Limiting speed	28000 r/min

Properties	
Bearing part	Complete bearing
Number of rows	1
Outer ring type	Machined (solid)
Aligning feature	Without
Cage	Sheet metal
Number of flanges, outer ring	2
Radial internal clearance	CN
Tolerance class	Normal
Material, bearing	Bearing steel
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	With
Indicative carbon footprint for new product	0.1 kg CO ₂

Logistics	
Product net weight	0.029 kg
eClass code	23-05-09-03
UNSPSC code	31171512

SKF drawings