



## SKF NJ 305 ECP

Single row cylindrical roller bearing, NJ design

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and one on the inner ring, NJ design bearings can accommodate axial displacement in one direction. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.

### Technical specifications

Dimensions	
Bore diameter	25 mm
Outside diameter	62 mm
Width	17 mm
Shoulder diameter of inner ring	38.1 mm
Shoulder diameter of outer ring	50.25 mm
Raceway diameter of inner ring	34 mm
Chamfer dimension	1.1 mm
Chamfer dimension	1.1 mm
Permissible axial displacement	1.3 mm

  

Abutment dimensions	
Diameter of spacer sleeve	31 mm
Diameter of spacer sleeve	32.5 mm
Diameter of shaft abutment	40 mm
Diameter of housing abutment	54.9 mm
Radius of fillet	1 mm

  

Calculation data	
SKF performance class	SKF Explorer
Basic dynamic load rating	46.5 kN
Basic static load rating	36.5 kN
Fatigue load limit	4.55 kN
Reference speed	12000 r/min
Limiting speed	15000 r/min
Minimum load factor	0.15
Limiting value	0.2
Calculation factor	0.6

  

Associated products	
Angle ring	HJ 305 EC

  

Performance	
Basic dynamic load rating	46.5 kN
Basic static load rating	36.5 kN
Reference speed	12000 r/min
Limiting speed	15000 r/min
SKF performance class	SKF Explorer

  

Properties	
Bearing part	Complete bearing
Axial displacement capability	In one direction
Number of rows	1
Locating feature, bearing outer ring	Without
Bore type	Cylindrical
Cage	Non-metallic
Number of flanges, outer ring	2
Number of flanges, inner ring	1

Loose flange	None
Radial internal clearance	CN
Tolerance class	Normal
Coating	Without
Sealing	Without
Lubricant	None
Relubrication feature	Without
Indicative carbon footprint for new product	0.86 kg CO <sub>2</sub> e

<b>Logistics</b>	
Product net weight	0.238 kg
eClass code	23-05-09-01
UNSPSC code	31171505

**SKF drawings**

