



SKF THGD 100

Инструмент SKF

Инструменты SKF для монтажа и демонтажа подшипников — ударные ключи, нагреватели, съёмники, гидравлические гайки. Обеспечивают безопасную и точную установку.

Характеристики

Размеры	
Dimensions (W x L x H)	90 x 45 x 114 mm
Свойства	
Рекомендуемые применения	For mounting bearings with the SKF Drive-up Method and for other applications where the pressure has to be determined with high accuracy
Suitable for Drive up method	Да
Special features	Dual scale dial, MPa/psi, Simultaneous display of actual and max pressure, Auto-off selectable, incl. Bar graph, Backlight, Battery level indication, Zero point correction, Swivel connection
Measurement method	Strain gauge
Display	LCD 4½ digit, 15 mm with back light illumination
Pressure range	Array bar
Measurement accuracy (+/-)	0.1 %
Resolution	0.01 MPa
Response time	10 ms
Housing outer diameter	90 mm
Connecting thread (G)	G 1/4
Battery	2x AA (LR6) Alkaline
Battery life	100 hr, with backlight; 1500 hrs, without backlight
Power source	Battery or alternatively USB-C (cable not included)
Auto switch off	30 min, off
Housing material	Glass fiber reinforced housing with rubber protection sleeve
Цвет	Blue, Black
Degree of protection (IP)	IP 67
Температурный диапазон	Array °C
Recommended storage temperature	Array °C
Relative humidity	<85%
Vibration resistance (IEC 60068-2-6)	10500 Hz / 5g
Shock resistance (IEC 60068-2-29)	25 mg/11 ms
Content	Gauge; 2x AA batteries; Rubber Protection sleeve; Instructions for use
Логистика	
Масса нетто	0.475 kg
Код eClass	23-05-19-01
Код UNSPSC	27112908