


SKF FYTJ 25 TF

Oval flanged ball bearing unit with set screw locking, cast iron housing, JIS



These oval flanged ball bearing units are compliant with Japanese Industrial Standards (JIS). They consist of an insert bearing, with an extended inner ring and set screw locking, and are suitable for applications where the direction of rotation is constant or alternating. The bearing is mounted in a cast iron housing, which can be bolted to a machine wall or frame. Ball bearing units can accommodate moderate initial misalignment, but normally do not permit axial displacement.

Technical specifications

General	
Compliance with standard	JIS
Purpose specific	For material handling applications
Material, housing	Cast iron
Sealing, bearing	Seal and flinger on both sides
Sealing type, bearing	Contact, standard
Sealing, unit	Without
Coating	Without

Dimensions	
Bore diameter	25 mm
Outer diameter of inner ring	33.74 mm
Width of housing	27 mm
Flange width	14 mm
Depth of centring recess	3.2 mm
Width of inner ring	34.1 mm
Overall bearing width	34.1 mm
Distance from locking device side face to thread centre	5 mm
Top external diameter	65 mm
Base external diameter	68 mm
Diameter of housing centering recess	63.5 mm
Overall height	130 mm
Centre distance between bolt holes	99 mm
Overall length	68 mm
Diameter of attachment bolt hole	16 mm
Distance from locking device side face to raceway centre	19.8 mm
Overall width	35.8 mm
Housing thread for grease fitting	1/4-28 UNF
Axial position of the housing thread	18 mm
Angular position of the housing thread	45 °
Diameter of head sphere of grease fitting	6.5 mm
Hexagonal key size for the grease fitting	7 mm
Thread of grease fitting	1/4-28 SAE-LT
Distance of dowel pins	81 mm
Axial offset of dowel pins	12 mm
Recommended diameter for dowel pins	2 mm
Attachment bolt diameter	14 mm
Shaft diameter	25 mm
Housing overall width	27 mm
Width, total	35.8 mm
Bearing width, total	34.1 mm

Calculation data	
Basic dynamic load rating	14 kN
Basic static load rating	7.8 kN
Fatigue load limit	0.335 kN
Limiting speed	7000 r/min
	Limiting speed with shaft tolerance h6

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m
Recommended diameter for attachment bolts, mm	14 mm
Recommended diameter for attachment bolts, inch	0.5625 in

Performance	
Basic dynamic load rating	14 kN
Basic static load rating	7.8 kN
Limiting speed	7000 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Housing type	Flanged
Flanged housing type	Oval
Number of bolt holes for fasteners	2
Fastening bolt hole type	Plain
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rubber seating ring	Without
Material, housing	Cast iron
Material, bearing	Bearing steel
Coating	Without
Sealing, bearing	Seal and flinger on both sides
Sealing type	Contact, standard
Sealing, unit	Without
Lubricant	Grease
Relubrication hole	With
Grease fitting	With

Logistics	
Product net weight	0.617 kg
eClass code	23-05-16-02
UNSPSC code	31171536

SKF drawings

