



SKF YAR 204-2RF/HV

Insert bearing with set screw locking and extended inner ring

Insert bearings are based on sealed deep groove ball bearings. This variant is suitable for applications with both constant and alternating directions of rotation. It has an inner ring extended on both sides and is locked onto the shaft by tightening two (set) screws on the inner ring, making it easy to mount.

Technical specifications

Dimensions	
Bore diameter	20 mm
Outside diameter	47 mm
Width of inner ring	31 mm
Width of outer ring	14 mm
Outside diameter of inner ring	28.2 mm
Distance face to thread centre	4.5 mm
Chamfer dimension of inner ring	0.6 mm
Distance from locking device side face to raceway centre	18.3 mm
Shaft diameter	20 mm
Width, total	31 mm
Width, inner ring	31 mm
Width, outer ring	14 mm

Calculation data	
Basic dynamic load rating	10.8 kN
Basic static load rating	6.55 kN
Fatigue load limit	0.28 kN
Limiting speed	5000 r/min
	Limiting speed with shaft tolerance h6
Calculation factor	13

Mounting information	
Set screw	M6x0.75
Hexagonal key size for set screw	3 mm
Recommended tightening torque for set screw	4 N·m

Associated products	
Rubber seating ring	RIS 204

Performance	
Basic dynamic load rating	10.8 kN
Basic static load rating	6.55 kN
Limiting speed	5000 r/min
Note	Limiting speed with shaft tolerance h6

Properties	
Retaining feature, inner ring	Set screws
Bore type	Cylindrical
Rolling elements	Balls
Outer ring type	Spherical
Inner ring extension	On both sides
Cage	Non-metallic
Rubber seating ring	Without
Material, bearing	Stainless steel
Coating	Without
Sealing	Seal and flinger on both sides
Sealing type	Contact, multiple

Lubricant	Grease
Relubrication feature	With
Logistics	
Product net weight	0.144 kg

SKF drawings

